

# Domekt R 900 V C6M


Maximal air flow, m <sup>3</sup> /h	953
Maximal air flow, l/s	265
Reference flow rate, m <sup>3</sup> /s	0,185
Reference pressure difference, Pa	50
SPI, W/(m <sup>3</sup> /h)	0,31
Thermal efficiency of heat recovery, %	82
Electric air heater capacity, kW / Δt, °C	2/8,8
Supply voltage, V	1~230
Maximal operating current HE, A	13,8
Power supply cable, mm <sup>2</sup>	3 × 1,5
Electric power input of the fan drive at maximum flow rate, W	241
Electric power input of the fan drive at reference flow rate, W	118
Noise power level, L <sub>WA,r</sub> dB(A)	46
Noise pressure level, L <sub>PA,r</sub> dB(A)	36
Filters dimensions B×H×L, mm	540×260×46
Unit dimensions B×H×L, mm	637×950×1070
Maintenance space, mm	1070
Unit weight, kg	110

NEW



## Performance

Unit with standard equipment



## Accessories




Closing damper	AGUJ-M-250+LF230/CM230
Silencer	A/D AGS-250-50-900-M
	B/C AGS-250-50-1200-M
Water heater	DH-250
PPU	PPU-HW-3R-15-0,63-W2
2-way valve (heater)	VVP47.10-0,63
Water cooler	DCW-0,9-6
2-way valve (cooler)	VVP47.15-2,5
Outdoor grill	LD-250
Water heater-cooler	DHCW-315
DX cooler	DCF-0,9-6
Cooling unit	MOU-18HFN8+KA8140

## Temperature efficiency

	Winter					Summer		
Outdoor temperature, °C	-23	-15	-10	-5	0	25	30	35
After heat exchanger, °C	13,6	15,1	16,0	16,9	17,9	22,6	23,5	24,4

indoor +22°C, 20 % RH

Shown as right (R1)



Shown as left (L1)

